

SAT 600 HPC

Technical specifications

Configuration	CCS
Communication	
Maximum charging current [A]	500
Charging mode	IEC 61851-1 IEC 61851-23 IEC 61851-24 ISO 15118 DIN 70121
Protocol	OCPP 1.6-J OCPP 2.0.1
General	
Housing	Steel with galvanised coating
Protection rating	IP 54 IK 10 IK 8 - Touchscreen
Overall dimensions (H x W x D) [mm]	2300 x 800 x 365
Weight [Kg]	~ 200
Operating temperature range [°C]	- 25 - +55 > 40 possible output power limitation
Operating altitude [m.a.s.l.]	≤ 2000
Compliance with standards	CE LVD 2014/35/UE EMC 2014/30/UE RED 2014/53/UE

SAT 600 HPC

Equipment

Configuration

CCS

Connectors

DC Connectors CCS 4,5m (up to 10m)

Uncooled DC connector Option

Cable Management System ✓

Housing

Colour RAL 9016 - Housing
RAL 9004 - Front panel

Additional branding Option

Anty graffiti Option

Meters

Output energy meter ✓

Input energy meter ✓

Eichrecht compliant ✓

Interface

Display 10" with integrated
RFiD card reader ✓

LED charging status
indication ✓

Payment system

CCV ✓

Payter Option

Communication

Data transfer GSM (LTE) EEP
GSM (LTE) Client
Ethernet

Catalog code

AVAILABLE ON Q3/2023

Preliminary data sheet

